

## Description:

Rust Kutter stops the oxidation process to prevent further rusting. Rust Kutter stops even the toughest rusting on ferrous metals, tools, farm equipment, railings, lawn furniture and truck beds.

## Directions:

Before using Rust Kutter, clean the area to be treated so that it is free from oils, grease or grime. Remove any loose paint or rust with a wire brush or sandpaper, but do not grind to bare metal. Shake well. Apply Rust Kutter to area and allow to dry. Drying can take up to 4 days depending on weather conditions and thickness of application. For difficult rust, agitate with a wire brush or sandpaper and repeat treatment. A black or white chalky film (dependent on the type of metal you are treating) will appear after product has dried. Product will not dry on areas that do not have rust. For these areas simply rinse and wipe off. Once dry you can apply a primer and paint.

## Caution:

This product will cause eye and skin irritation. Always wear eye and skin protection when handling. May harm or destroy clothing and fabrics. Prevent prolonged exposure, which may result in eye/skin damage. Do not use in confined spaces or near ignition sources. Do not breathe fumes.



0  
7 L  
1 4  
6 0  
2 3  
0 2

See side for Additional Precautionary Statements

**Net Contents: 1QT (946.3ml)**

**SAVES TOOLS & STOPS OXIDATION!**

# RUST KUTTER<sup>®</sup>

**STOPS RUST!**



**KEEP OUT OF REACH OF CHILDREN  
DANGER**

## First Aid:

If inhaled- Remove victim to fresh air and keep at rest in position comfortable for breathing. If on skin- Remove all contaminated clothing. Rinse skin with water immediately. If in eyes- Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If ingested- Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor if you feel unwell.

## Tips To Remember:

- Apply at temperatures between 50°F - 90°F. Not intended for surface that will exceed 220°F.
- Test in inconspicuous area before treating entire surface. Could dull or lighten painted surfaces.
- Product must dry at least 24 hours before applying oil based paints and at least 72 hours for aerosols and lacquer based paints.
- Treated areas will turn black or white and chalky. Agitate with a wire brush or sandpaper and reapply on heavily rusted areas.
- It is best to apply two or three coats. Allow area to completely dry between coats.
- Non-zinc based primers are recommended but not required.
- Do not sand surface before painting. This may expose bare, untreated metal.
- Rust must be present for product to work.
- If bleed-through appears, reapply Rust Kutter.

## Contains:

Proprietary blend of phosphoric acid and citric acid



Manufactured by:  
Sanco Industries, Inc.  
P.O. Box 11617  
Fort Wayne, IN 46859 USA  
www.rustkutter.com