

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 12/17/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Trade name : Stock Plex Stock Tank Algae Control

1.2. Other means of identification

Other means of identification : EPA Reg Number 83190-1-72838
Liquid Copper

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Algae control

1.4. Supplier's details

Sanco Industries, Inc.
1819 S. Calhoun St.
Fort Wayne, IN 46802
T +1 260) 426-6281
info@sancoindustries.net

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 202588
Back-up Emergency Number: +1 703-741-5970 (Washington, DC)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 1	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Carcinogenicity, Category 1A	H350	May cause cancer.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage
H350 - May cause cancer.

Precautionary statements (GHS US) : Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dusts or mists.
Wash hands, forearms and face thoroughly after handling.
Wear protective gloves, protective clothing, eye and face protection.
If swallowed: rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

If inhaled: Remove person to fresh air and keep comfortable for breathing.
If exposed or concerned: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Store locked up.
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Copper sulfate	CAS-No.: 7758-99-8	19.8	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Sulfuric acid	CAS-No.: 7664-93-9	2.68	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318 Carc. 1A, H350 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but, not mouth-to-mouth. If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Lay in a stable manner on victim's side. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician.

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately transport the casualty to an eye doctor / hospital. Continue rinsing with water during transport.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause cancer. Inhalation of vapors may cause respiratory irritation.
Symptoms/effects after skin contact	: Causes severe burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Most Important Symptoms/Effects	: Corrosive effects. Risk of irreversible damage to affected area.
Chronic symptoms	: May cause cancer.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Transfer to hospital rapidly.
-----------------------------------	---------------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Corrosive vapors.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Cool affected containers with flooding quantities of water. Move containers from fire area if it can be done without personal risk. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid all personal contact including breathing in the mist, spray, vapors. Avoid contact with eyes, skin and clothing. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
------------------	--

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Avoid breathing mist, spray, vapors. Avoid contact with skin, eyes and clothing. Evacuate the danger area. If outdoors, move to an area upwind of the danger area. Only qualified personnel equipped with suitable protective equipment may intervene. Prevent other non-emergency personnel from entering the danger area. Ventilate spillage area.

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Do not touch or walk on the spilled product. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up in non-combustible inert absorbent (ex. sand, earth, or vermiculite) and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spilt product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13: "Disposal considerations".

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Avoid breathing mist, spray, vapors. Avoid contact with eyes, skin and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store in a cool, dry and well-ventilated area away from incompatible substances.
Incompatible materials	: Strong acids. Strong bases. Reducing agents. Powdered metals.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Stock Plex Stock Tank Algae Control	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sulfuric acid
ACGIH® TLV® TWA	0.2 mg/m³ (T - Thoracic particulate matter)
Remark (ACGIH®)	TLV® Basis: Mucostasis; Pulm func. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Stock Plex Stock Tank Algae Control	
USA - OSHA - Occupational Exposure Limits	
Local name	Sulfuric acid
OSHA PEL TWA	1 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Sulfuric acid
NIOSH REL 10h TWA	1 mg/m ³
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Sulfuric acid (7664-93-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sulfuric acid
ACGIH® TLV® TWA	0.2 mg/m ³ (T - Thoracic particulate matter)
Remark (ACGIH®)	TLV® Basis: Mucostasis; Pulm func. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Sulfuric acid
OSHA PEL TWA	1 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Sulfuric acid
NIOSH REL 10h TWA	1 mg/m ³
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Copper sulfate (7758-99-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	1 mg/m ³ (as Cu)
USA - OSHA - Occupational Exposure Limits	
Local name	Copper Sulfate
OSHA PEL TWA	1 mg/m ³ (as Cu)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	1 mg/m ³ (as Cu)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Environmental exposure controls	: Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Chemically impervious gloves as described by OSHA's hand protection regulations in 29 CFR 1910.138

Eye protection:

Chemical goggles or face shield. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Colorless, syrupy liquid.
Color	: Blue
Odor	: Odorless
Odor threshold	: No data available
pH	: 0.2 – 1.5
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 104 °C / 219.2 °F
Flash point	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.19
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Extremely high or low temperatures. Direct sunlight. Incompatible materials.

10.5. Incompatible materials

Strong acids. Strong bases. Reducing agents. Powdered metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Carbon monoxide. Carbon dioxide. Corrosive vapors.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Copper sulfate

LD50 oral rat	960 mg/kg
LD50 oral	960 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	9.92 mg/l

Skin corrosion/irritation : Causes severe skin burns.
pH: 0.2 – 1.5

Sulfuric acid

Specific Concentration Limit, Skin Corrosion, Category 1A	≥ 15 %
Specific Concentration Limit, Skin Irritation, Category 2	≥ 5 - < 15 %

Copper sulfate

pH	4
----	---

Serious eye damage/irritation : Causes serious eye damage.
pH: 0.2 – 1.5

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Sulfuric acid	
Specific Concentration Limit, Eye Irritation, Category 2	≥ 5 - < 15 %
Copper sulfate	
pH	4

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : May cause cancer.

Sulfuric acid	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Sulfuric acid	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause cancer. Inhalation of vapors may cause respiratory irritation.

Symptoms/effects after skin contact : Causes severe burns.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Most Important Symptoms/Effects : Corrosive effects. Risk of irreversible damage to affected area.

Chronic symptoms : May cause cancer.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects

Sulfuric acid	
LC50 - Fish [1]	16 – 28 mg/l
EC50 - Crustacea [1]	> 100 mg/l
EC50 72h - Algae [1]	> 100 mg/l
NOEC (chronic)	0.15 mg/l
NOEC chronic fish	0.31 mg/l
Copper sulfate	
EC50 - Crustacea [1]	0.00272 mg/l

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.2. Persistence and degradability

Stock Plex Stock Tank Algae Control

Persistence and degradability	Not established.
-------------------------------	------------------

Sulfuric acid

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Copper sulfate

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
Not applicable	3264	3264
14.2. Proper Shipping Name		
Corrosive liquid, acidic, inorganic, n.o.s. (Sulfuric acid)	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Sulfuric acid)	Corrosive liquid, acidic, inorganic, n.o.s. (Sulfuric acid)
14.3. Transport hazard class(es)		
8	8	8
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
	Dangerous for the environment: Yes Marine pollutant: Yes	

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	IMDG	IATA
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters",53 - Stow "separated from" alkaline compounds,58 - Stow "separated from" cyanides

IMDG

Special provision (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: SW2
Segregation (IMDG)	: SGG1, SG36, SG49
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 8L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Copper sulfate	CAS-No. 7758-99-8	19.8%
----------------	-------------------	-------

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Sulfuric acid	CAS-No. 7664-93-9	2.68%
---------------	-------------------	-------

Sulfuric acid (7664-93-9)

CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

15.2. International regulations

CANADA

Sulfuric acid (7664-93-9)

Listed on the Canadian DSL (Domestic Substances List)

Copper sulfate (7758-99-8)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Sulfuric acid (7664-93-9)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product can expose you to Sulfuric acid mists, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
-----------	----------------------------

Sulfuric acid(7664-93-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
--------------------------	---

SECTION 16 Other information

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Issue date : 12/17/2025

Full text of hazard classes and H-statements

H290	May be corrosive to metals
H302	Harmful if swallowed

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements	
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation
H350	May cause cancer.
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms	
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstracts Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)

Stock Plex Stock Tank Algae Control

Safety Data Sheet

According to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Abbreviations and acronyms	
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organization for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.